

BUILT BY **THE BEST** TO WITHSTAND THE WORST.

Product data sheet









Typical use:

For the storage of a basket type stretcher. This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a Stainless Steel 'L' handle to pull the door open to guarantee fast access even when wearing gloves.





Manufactured in the UK

Standard specification:

Dimensions (mm)

Height x width x depth: 2350 x 820 x 282

Aperture: 2175H x 615W

Internal depth: 220

Weight Kg: 32Kg

Material specification:

Colour: Green RAL 6029

Material: Lloyds approved composites with UV stabi-

lised gelcoat

Hinges: Stainless Steel

Handle: Stainless Steel 'L' handle

Seal: FPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel

316 Stainless steel 3 way locking

Double doors





For pricing or further information, please contact our United Kingdom office

Britannia Safety

Tel: +44 (0)1404 41294

Email: enquiries@britanniasafety.com

ALL **PRODUCT**, **PRODUCT SPECIFICATIONS** AND DATA ARE **SUBJECT TO CHANGE WITHOUT NOTICE** TO IMPROVE RELIABILITY, FUNCTION OR **DESIGN** OR OTHERWISE. ... It is the customer's responsibility to validate that a product with the properties described in the **product specification** is suitable for use in a particular application.